

correl A 3

Detailed Description of the Preferred Embodiments--.

---

**IN THE CLAIMS**

Please amend the claims as follows. A marked-up copy is attached.

---

A4 1. (amended) A gas generator comprising at least one first body, comprising means for the generation of gas and one or more reaction products, and at least one spatially separated second body, comprising means for the generation of a neutralisation agent, wherein means are present for passing said neutralization agent through the said first body, to neutralize one or more reaction products from the generation of gas in the said first body, and wherein means are present for operating the generation of a neutralisation agent in the second body at a spatial interval and optionally a temporal interval from the generation of gas in the first body.

2. (amended) The gas generator according to claim 1, wherein the said means for generating a gas comprise components that generate nitrogen, oxygen, hydrogen or combinations thereof.

3. (amended) The gas generator according to claim 2, wherein the means in the first body comprise a gas-penetrable

solid material comprising a gas source, cementing agent and optionally a heat absorbing mixture, wherein the solid material has a porosity of 35-60 wt.%.

4. (amended) The gas generator according to claim 1, wherein said first body comprises means for generating nitrogen.

5. (amended) The gas generator according to claim 1, wherein the reaction products comprise slag containing sodium.

cont 4  
6. (amended) The gas generator according to claim 1, wherein the second body contains a gas source and a neutralising agent.

7. (amended) The gas generator according to claim 1, wherein the neutralisation agent is sulphur.

8. (amended) The gas generator according to claim 1, wherein the combined amounts of the gas sources in the first and second body comprises 50-80 wt.% drawn on the total weight of the gas generator and the amount of neutralisation agent in the second body comprises 47-90 wt.% of neutralisation agent, drawn on the weight of the second body.

9. (amended) The gas generator according to claim 1, wherein the second body is between 17 and 35 wt.% drawn on the total weight of the gas generator.

10. (amended) The gas generator according to claim 1, wherein the second body contains 10 to 53 wt.% of the nitrogen source and 47 to 90 wt.% of the neutralisation agent.

11. (amended) The gas generator according to claim 1, wherein the generated gases are cooled by a heat absorbing material.

12. (amended) The gas generator according to claim 1, whereby the heat absorbing material is included in the first body.

13. (amended) The gas generator according to claim 1, wherein downstream from the first body means are present for cooling and/or filtering the gases.

14. (amended) The gas generator according to claim 1, wherein said means also comprise neutralising agents for contaminants entrained in the gas.

cont A4

15. (amended) The gas generator according to claim 1, wherein the said first and second bodies are contained within one container, said container having at least one outlet for generated gas.

16. (amended) A process for the generation of gases comprising the steps of:

decomposition of a gas-penetrable porous solid material in a first body, whereby gas and other reaction products are generated at a decomposition front;

passing the gas through said porous solid material;

generating a neutralisation agent in a second body, wherein the second body is spatially separated from the first body;

passing the neutralisation agent through said porous solid material;

neutralising the said other reaction products in the first body by reaction with the neutralisation agent;

maintaining a temporal and/or spatial interval between the decomposition front of the first body and a neutralisation front obtained by passing the neutralisation agent from the second body into the first body.

17. (amended) The process according to claim 16, wherein the generated gases are cooled by passing the gases through the

porous solid material in the same direction as the reaction front is moving.

18. (amended) The process according to claim 16, wherein heat is absorbed in the porous body, which heat is formed in the decomposition of the gas-penetrable porous solid material.

19. (amended) The process according to claim 11, wherein the amounts of heat formed and absorbed are such that the generated gas is cooled to a temperature below 150°C.

cancel 4  
20. (amended) The process according to claim 17, wherein the heat absorbed in the porous solid material maintains the temperature necessary for decomposition of the gas-penetrable porous solid material.

21. (amended) The process according to claim 16, wherein the generated gases are passed through a filter and/or cooling means, downstream from the generation of the gases, said filter and/or cooling means optionally containing further neutralisation means.

---

A5 22. (new) The generator according to claim 4, wherein the means for generating nitrogen is azide.